


CARBOPOMP/EC10NL 22N

Per mandata di carburanti, gasolio, benzine senza piombo ed eco diesel. Utilizzato sui motori a combustione interna di autoveicoli, autoveicoli industriali e trattori


Long length fuel delivery hose suitable for diesel, unleaded fuel and ecodiesel. Used in cars and industrial vehicles.



Caratteristiche tecniche

Sottostrato	Liscio in gomma nera resistente ai carburanti con contenuto aromatico non superiore al 50% ed alle benzine senza piombo con contenuto massimo: di MTBE 5%, di composti ossigenati 15%
Sottostrato	Inserzioni di filati sintetici ad alta resistenza.
Copertura	In gomma nera resistente ai lubrificanti, ai carburanti, alle alte temperature ed all'invecchiamento. Superficie liscia stampata.
Pressione di esercizio	10 bar
Pressione di scoppio	30 bar
Temperatura	- 20 °C + 120 °C
Marcatura	 CARBOPOMP/ECO NL W.P. 10 BAR [Ø] (in lettere verdi)

Technical Characteristics

Tube	<i>Black smooth rubber, suitable for petroleum products with max. 50% aromatic content and for unleaded fuel with max. 5% MTBE and 15% oxygenated compounds.</i>
Reinforcement	<i>High strength textile yarn</i>
Cover	<i>Black, smooth rubber, oil, temperature and ageing resistant.</i>
Working Pressure	10 bar
Nominal Burst Pressure	30 bar
Temperature	- 20 °C + 120 °C
Marking	 CARBOPOMP/ECO NL W.P. 10 BAR [Ø] (in green letters)

Disponibile anche nella versione:

CARBOPOMP/EC10NL 26N: con copertura in gomma autoestinguente

Available also in the following version:

CARBOPOMP/EC10NL 26N: cover in self-extinguishing rubber

Misure / Sizes

Diametro interno <i>Inner Diameter</i>	Spessore parete <i>Wall Thickness</i>	Diametro esterno <i>Outside Diameter</i>	Peso teorico <i>Weight</i>
mm	mm	mm	Kg/m
5	3,5	12	0,110
6	3,5	13	0,125
7	3	13	0,140

Diametro interno <i>Inner Diameter</i>	Spessore parete <i>Wall Thickness</i>	Diametro esterno <i>Outside Diameter</i>	Peso teorico <i>Weight</i>
mm	mm	mm	Kg/m
8	3,25	14,5	0,150
10	3,25	16,5	0,180
13	3,5	20	0,270