


CASER/15NL C4N

Tubo per mandata di acqua calda conforme agli standard **F.D.A.**


Long length hot water delivery hose complying with **FDA** standards.



Caratteristiche Tecniche

Sottostrato	Liscio in gomma nera alimentare resistente alle alte temperature.
Rinforzi	Inserzioni di filati sintetici ad alta resistenza.
Copertura	In gomma nera resistente all'abrasione, al calore, agli agenti atmosferici ed all'ozono. Superficie liscia stampata.
Pressione di esercizio	15 bar
Pressione di scoppio	45 bar
Temperatura	- 35 °C + 110 °C
Marcatura	 FOOD QUALITY D.M. 21 / 3 / 73 e 18 / 6 / 79 t°. 110 °C (in lettere bianche)

Technical Characteristics

Tube	Black smooth food quality rubber, resistant to high temperatures
Reinforcement	High tensile synthetic yarns
Cover	Black smooth rubber, abrasion, heat, ozone and weathering resistant.
Working Pressure	15 bar
Nominal Burst Pressure	45 bar
Temperature	- 35 °C + 110 °C
Marking	 FOOD QUALITY D.M. 21 / 3 / 73 e 18 / 6 / 79 t°. 110 °C (in white letters)

Disponibile anche nella versione:

CASER/15 BL C4B: con copertura in gomma blu.

Available also in the following version:

CASER/15BL C4B: with blue rubber cover

Misure / Sizes

Diametro interno Inner Diameter	Spessore parete Wall Thickness	Diametro esterno Outside Diameter	Peso teorico Weight
mm	mm	mm	Kg/m
5	3,50	12	0,135
8	3,50	15	0,160
10	3,50	17	0,190
11	4	19	0,262

Diametro interno Inner Diameter	Spessore parete Wall Thickness	Diametro esterno Outside Diameter	Peso teorico Weight
mm	mm	mm	Kg/m
12	3,75	19,5	0,250
12	4,75	21,5	0,349
19	6	31	0,510